

QX系列直动式电磁阀

2/2,3/2 WAY DIRECT-ACTING SOLENOID VALVE



型号 Model	连接尺寸 Port Size	流量孔径 Orifice Size	使用压差范围 Pressure Difference	工作介质 Working Medium
QX22-08	ZG1/4"	4mm	0~0.9MPa	空气、水、燃气 Air, Water, Gas
QX22-10	ZG3/8"			
以下流量孔需定制				
—		2.4mm	0~2.0MPa	—
—		5mm	0~0.6MPa	—

型号 Model	孔径 Orifice Size		连接尺寸 Port Size	使用压差范围 Pressure Difference	工作介质 Working Medium
	顶部 Top	阀体 Body			
QX23-08	2.3	1.6	ZG1/4"	0~0.9MPa	空气、水、燃气 Air, Water, Gas
QX23-10	2.3	1.6	ZG3/8"		

KLTJ二位二通常闭直动可调式蒸汽电磁阀

KLTJ SERIES ADJUSTABLE STEAM SOLENOID VALVE



型号 Model	接管口径 Port Size	公称通径 Orifice Size	使用压差范围 Pressure Difference	工作温度 Operating Temp.
KLTJ	ZG1/4"	2.0mm (需定制) Need to be customized	0 ~ 1.0MPa	-10 ~ 160℃
		2.7mm		
		3.0mm (需定制) Need to be customized		

XF系列二位二通先导膜片式电磁阀

XF SERIES 2/2 WAY PILOT ACTING SOLENOID VALVE



型号 Model	接管口径 Port Size	通径 Orifice Size	使用压差范围 Pressure Difference	工作温度 Operating Temp.
XF	ZG1/4"	12mm	0.05~1.0MPa	NBR: -5~80℃; EPDM: -5~120℃; VITON: -10~150℃
	ZG3/8"			
	ZG1/2"			

KLG/A/D系列脉冲阀

KLG /A /D SERIES PULSE SOLEOID VALVE



型号 Model	工作介质 Working Medium	使用压差范围 Pressure Difference	工作温度 Operating Temp.	电压 Voltage
KLG-Z-15	清洁空气 Clean Air	0.3~0.6MPa	-25~55℃	AC110V AC220V DC24V
KLG-Z-76S				
KLG-Y-50S				
KLA-Z-25J				
KLA-Z-25				
KLD-Z-25				

UPVC、CPVC电磁阀

UPVC,CPVC SERIES SOLENOID VALVE



型号 Model	接管口径 Port Size	工作介质 Working Medium	使用压差范围 Pressure Difference	工作温度 Operating Temp.
2W15ZP	1/2"	硫酸、盐酸浓度 <10% Sulfuric acid, Hydrochloric acid density <10%	0.01~0.6MPa	Max.+50℃
2W20ZP	3/4"			
2W25ZP	1"			
2W32ZP	1 1/4"			
2W40ZP	1 1/2"			
2W50ZP	2"			



型号 Model	接管口径 Port Size	工作介质 Working Medium	使用压差范围 Pressure Difference	工作温度 Operating Temp.
2W15ZC	1/2"	硫酸浓度 <60%、任意盐 酸浓度均适合 Sulfuric acid density <60%, Any hydrochloric acid	0.01~0.6MPa	Max.+95℃
2W20ZC	3/4"			
2W25ZC	1"			
2W32ZC	1 1/4"			
2W40ZC	1 1/2"			
2W50ZC	2"			

2W15ZPF (法兰/Flange) 2W25ZPF (法兰/Flange) 2W40ZPF (法兰/Flange)
2W15ZCF (法兰/Flange) 2W25ZCF (法兰/Flange) 2W40ZCF (法兰/Flange)

聚四氟(塑料王)电磁阀

PTFE MATERIAL SOLENOID VALVE



型号 Model	接管口径 Port Size	流量孔径 Orifice Size	使用压差范围 Pressure Difference	工作温度 Operating Temp.
ZCF15	1/2"	15mm	0.01~0.6(MPa)	Max.+180℃
ZCF20	3/4"	20mm		
ZCF25	1"	25mm		
ZCF32	1 1/4"	32mm		
ZCF40	1 1/2"	40mm		
ZCF50	2"	50mm		
ZCF65	2 1/2"	60mm		

ZBSF系列全不锈钢电磁阀

ZBSF STAINLESS STEEL SOLENOID VALVE



型号 Model	公称通径 Port Size	工作介质 Working Medium	使用压差范围 Pressure Difference	工作温度 Operating Temp.
ZBSF-1	10mm, 15mm, 20mm	腐蚀性流体, 超净流体, 食用流体 Corrosive fluid, clean fluid, edible fluid	1.6MPa	ZBSF-1(1Y): ≤60℃, ZBSF-2(2Y): ≤280℃
ZBSF-1Y	25mm, 32mm, 40mm			
ZBSF-2	50mm, 65mm, 80mm			
ZBSF-2Y	100mm, 125mm, 150mm			